INCEILING P4

InCeiling Premium Series

The InCeiling P4 built-in speakers are part of the InCeiling Premium series and expand the portfolio of high-quality ceiling-mounted solutions. New membrane technology with ATB bass/midrange drivers (aluminium titanium black) ensures precise and dynamic music reproduction, while the swivelling tweeter system with AB domes (aluminium black) enables targeted sound dispersion. Installation is easy thanks to Easy-Lock technology, the supplied installation template and Phoenix-compatible connectors. The frameless metal grilles with magnetic fastenings can be painted to match the surroundings, allowing them to be integrated almost invisibly into any wall or ceiling.







MECHANICAL PARAMETERS

Description		Built-in Loudspeaker
Principle		2-way
Connection		4-pin PCB Connector with Loop-Through Output max. Speaker Cable Cross-Section 12 AWG (4mm²)
Driver Sizes	1 ×	25 mm, AB Tweeter
	1 ×	135 mm, ATB Woofer/Midrange
Diameter		177 mm
Installation Cut-Out		152 mm
Installation Depth		74 mm
Ceiling Thickness		37 mm
Weight		1 kg

PRODUCT INFORMATION







Swivel tweeter and level adjustment

The compact ATB chassis made of aluminium-titanium composite material ensures precise impulse fidelity and natural timbres. The tweeter is swivelling, allowing precise alignment of the high-frequency range for an optimal listening position.
In addition, the integrated level adjustment allows fine tuning of the high frequencies (+/–) to optimally adjust the sound to the room acoustics.





ELECTRICAL PARAMETERS

Frequency Response (-3dB/-10dB)	71...38.000 Hz / 48...40.000 Hz
Transmission Range	50...40.000 Hz
Crossover Frequency	3.000 Hz
Coverage Angle (1kHz – 8kHz)	155° conical
Sensitivity (2,83 V/1 m)	84 dB
Maximum Sound Pressure Level	103 dB
Nominal / Music Power Capability	45 / 100 watt
Nominal Impedance	8 Ohm
Minimum Impedance	7,1 Ohm

ACOUSTIC PARAMETERS

Dispersion Angle vs. Frequency



Dispersion Characteristics 2kHz-16kHz



Dispersion Characteristics 125Hz-1kHz



Frequency Response 1 m, Angle 0–30°



Frequency Response 1 m, on axis



Impedance



All measurements were made using KLIPPEL R&D System.