Monitor 50

MONITOR AUDIO

Iconic British Sound, Designed for Every Listener.

The Monitor 50 is a perfect introduction to Monitor Audio's premium British high fidelity, delivering remarkable performance from a compact footprint. Its precision C-CAM metal drivers, technology Monitor Audio has pioneered for over 40 years, work with high-efficiency motor systems to deliver clean, controlled sound. Our signature through-bolt construction counteracts driver resonance and strengthens the cabinet from within, while the rigid, painted 25 mm-thick baffle and refined cabinet provide a stable, acoustically inert platform. Paired with a 25mm Gold C-CAM tweeter for lifelike detail and a punchy 5-inch mid-bass driver, the Monitor 50 might be small in size, but it's big in capability. The ideal first step into the world of Monitor Audio.





Monitor 50

The Monitor 50 is designed for listeners taking their first step into the Monitor Audio brand. A compact, stylish bookshelf speaker that will fit effortlessly into modern living spaces. Perfect for bedrooms, student flats, home offices or smaller lounges, they offer a genuine high-fidelity upgrade without the need for large systems or big budgets. Whether streaming playlists, watching films, gaming, or diving deeper into music discovery, the Monitor 50 delivers an authentic Monitor Audio experience in a small, accessible, and brilliantly versatile package.

Features at a glance:

- Two-way design
- 1 x 25 mm C-CAM Gold Dome Tweeter with UD Waveguide
- 1 x 5" C-CAM Bass-mid Driver
- New crossover design
- Ported cabinet design featuring HiVe port technology
- Available in Black



Model	Monitor 50
System Format	2-Way
Frequency Response, In-Room (-6dB)	40 Hz – 30 kHz
Nominal Impedance	8 Ohms
Minimum Impedance (20Hz to 20kHz)	4.4 Ohms
Maximum Peak SPL (AES75, Z-weighted)	107 dBA (pair)
Continuous Power Handling (CTA 426-B)	80 W
Recommended Amplifier Power (RMS, Music Signal)	20 – 80 W
Bass Alignment	Ported - HiVe II
Crossover Frequency	2.5 kHz
Drive Unit Complement	1 x 1" (25 mm) C-CAM Gold Dome Tweeter with UD waveguide 1 x $5^{1/2}$" (138 mm) C-CAM Bass-mid driver
External Dimensions with all accessories fitted (H x W x D)	281 x 166 x 265 mm ($11^{1/16}$ x $6^{9/16}$ x $10^{7/16}$ ")
Packed Dimensions (H x W x D)	371 x 630 x 272 mm ($14^{5/8}$ x $24^{13/16}$ x $10^{11/16}$ ")
Net Weight (Each)	5.0 kg (11 lb)
Packaged Gross Weight (Pair)	11.7 kg (25 lb 12 oz)
Finishes	Black
Sold as	Pair
RRP (GBP, EUR, USD)	£300 / €400 / $500
EAN	5061070621118

Listen Again.

Information in this document is confidential and subject to change. Pricing is approximate and subject to change.